



OLD WORLD INDUSTRIES, INC.
4065 COMMERCIAL AVENUE
NORTHBROOK, ILLINOIS 60062-1851
708-559-2000 • FAX 708-559-1329

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Effective Date: 4/1/03

Old World Industries, Inc.
4065 Commercial Avenue
Northbrook, Illinois 60062
Phone: 847-559-2000

Emergency Phone: 1-800-424-9300 [CHEMTREC]

PRODUCT: PEAK® PA RUNWAY DEICING FLUID

Chemical Name: Aqueous Potassium Acetate Solution

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Components</u>	<u>Percent</u>	<u>TLV (Units)</u>	<u>CAS #</u>
Potassium Acetate	~50.0%	None established	127-08-2
Water	~49.0%	None established	7732-18-5
Corrosion Inhibitors	<1.0%	None established	

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This product is not a hazard as defined by OSHA Communication Standard (29 CFR Section 1910.1200). Base ingredient is listed in TSCA Inventory.

		<u>Key</u>
NFPA Rating	-	0 - Minimal
Health	1	1 - Slight
Fire	0	2 - Moderate
Reactivity	0	3 - Serious
		4 - Severe

POTENTIAL HEALTH EFFECTS:

Eye Contact: This substance is slightly irritating to the eyes and could cause prolonged (days) impairment of your vision. The degree of the injury will depend on the amount of material that gets into

the eye and the speed and thoroughness of the first aid treatment. Signs and symptoms may include pain, tears, swelling, redness and blurred vision.

- Skin Contact: This substance is not expected to cause prolonged or significant skin irritation. The systemic toxicity of this substance has not been determined. However, it should be practically non-toxic to internal organs if it gets on the skin.
- Inhalation (Breathing): This material does not present an inhalation hazard.
- Ingestion (Swallowing): Ingestion may cause irritation of the digestive tract which may result in nausea, vomiting and diarrhea.
- Exposure: This product contains potassium salts which is an acute risk. Ingestion of large amounts (25 or more grams) of potassium salts usually causes a person to vomit. If the person is not suffering from a pre-existing kidney and/or cardiac condition, the absorbed potassium salt is excreted in the urine.

4. FIRST AID INFORMATION

- Eye Contact: For direct contact, flush the affected eye(s) with clean water for 15 minutes or until irritation subsides. If irritation or redness persists, seek medical attention.
- Skin Contact: Cleanse affected area(s) by washing with mild soap and water.
- Inhalation (Breathing): Since this material is not expected to be an immediate inhalation problem, no first aid procedures are required.

5. FIRE AND EXPLOSION INFORMATION

- Flash Point: Not Flammable
- Ignition Temperature: N/A
- Extinguishing Media: Non-flammable. After water evaporates, remaining material will burn. Use alcohol-type or universal-type foams applied by manufacturer's recommended techniques for large fires. Carbon dioxide or dry chemical for small fires.

6. SPILL AND DISPOSAL INFORMATION

- Measure after Spillage: Before handling any spills, always observe the safety precautions described in Section 3. Spills can be removed with a suitable absorbent, (i.e., sand or sawdust). The rest can be removed with water.
- Disposal: If product should spill or become unsuitable for normal deicing applications, it may be disposed of in sanitary landfill in accordance with local, state, and federal regulations.
- This product is not listed as a hazardous waste and does not classify as a RCRA hazardous waste.

7. HANDLING AND STORAGE

Store in recommended tanks or containers away from strong oxidizers or other chemicals. Use normal operational procedures for non-hazardous product.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection:	No special respiratory protection is normally required.
Ventilation:	No special ventilation is necessary.
Protective Gloves:	The use of gloves impermeable to the specific material handled is advised to prevent skin contact and possible irritation.
Eye Protection:	Approved eye protection to safeguard against potential eye contact, irritation or injury is recommended.
Other Protective equip:	It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appx. Boiling Point:	116°C (241°F)
Freezing Point:	>75 F (60 C)
Volatility/Vol %:	None
Vapor Pressure (mm Hg):	NDA
Vapor Density (Air=1):	NDA
Solubility in H ₂ O:	Complete
Appearance:	Clear colorless to light straw without blue dye. With blue dye, it is transparent blue.
Odor:	Very minimal
Specific Gravity H ₂ O =1):	1.265 - 1.285 @ 60°F
Viscosity:	20 - 25 cp @ 0°C
Evaporation Rate:	NDA
pH:	9.3 – 10.3

10. STABILITY/REACTIVITY

Chemical Stability:	This material is stable.
Conditions to Avoid:	None
Incompatible Materials:	May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
Decomposition Products:	None known
Hazardous Polymerization:	Will not occur

11. TOXICOLOGY INFORMATION

Acute Oral Toxicity LD₅₀ 5000mg/kg (rats)
Skin Irritation: Non-irritant
Eye Irritation: Non-irritant
Fish Toxicity LC₅₀ >500mg/L (Daphnia magna)
>1000mg/L (Pimephales promelas)

This material is toxicologically harmless and is not considered a carcinogen.

12. TRANSPORTATION INFORMATION

D.O.T. Proper Shipping Name/Hazard: Not Regulated

13. REGULATORY INFORMATION

Reportable quantity (RQ), EPA Regulation 40 CFR 302 (CERLA Section 102): N/A
Threshold Planning Qty. (TPQ), EPA Regulation 40 CFR 355 (SARA Sections 301-304):
N/A
Toxic Chemical Release Reporting, EPA Regulation 40 CFR 372 (SARA Sections 311-313):
N/A

14. OTHER INFORMATION

Contact: Karen Engelbrecht, Technical Product Manager Phone: 847-559-2000

Old World Industries, Inc. makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries, Inc., as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Old World assume any liability arising out of the use by others of this product referred to herein. The data in the MSDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.